

Safety Data Sheet

Issue Date: 01-Jun-1990

Revision Date: 16-Mar-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name QUARRY TILE CLEANER

Other means of identification

SDS # CTI-057

UN/ID No UN1760

Recommended use of the chemical and restrictions on use

Recommended Use Tile cleaner.

Details of the supplier of the safety data sheet

Supplier Address

Chemtron Incorporated
7350 C Lockport Place
Lorton, Virginia 22079

Emergency Telephone Number

Company Phone Number Information: 703-550-7772

Emergency Telephone (24 hr) Chemtrec 1-800-424-9300 (North America) 1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Appearance Brownish liquid

Physical State Liquid

Odor Musty

Classification

| | |
|-----------------------------------|---------------------------|
| Skin corrosion/irritation | Category 1 Sub-category B |
| Serious eye damage/eye irritation | Category 1 |

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger

Hazard Statements

Causes severe skin burns and eye damage



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a poison center or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a poison center or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a poison center or doctor/physician

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|---|------------|----------|
| Ethylene Glycol Monobutyl Ether | 111-76-2 | <5 |
| Monoethanolamine | 141-43-5 | <5 |
| Potassium hydroxide | 1310-58-3 | <5 |
| Dipropylene Glycol Monomethyl Ether (DPM) | 34590-94-8 | <5 |
| Sodium dodecyl benzene sulphonate | 25155-30-0 | 1-2 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

| | |
|---------------------|--|
| Eye Contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Immediately call a poison center or doctor/physician. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice. |
| Inhalation | Remove to fresh air. Call a physician or poison control center immediately. |
| Ingestion | Get medical attention immediately. |

Most important symptoms and effects

| | |
|-----------------|--|
| Symptoms | Causes severe skin burns and eye damage. Inhalation of vapors may cause damage to respiratory tract. Ingestion may result in mucosal damage. Ingestion may cause severe burns to mouth, throat or stomach. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|------------------------|
| Notes to Physician | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable. This product is corrosive.

Hazardous Combustion Products When strongly heated, as in a fire, this product may produce carbon dioxide, carbon monoxide and oxides of nitrogen.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Neutralize with a dilute inorganic acid. Absorb with inert material or sweep up, and then place in suitable container for chemical waste.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. This is an industrial cleaning compound. Do not mix with anything but water. Do not breathe vapors or spray mist. Wash face, hands, and any exposed skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Do not store at elevated temperatures. To insure maximum shelf life, store at a normal room temperature. Store locked up. Store away from incompatible materials.

Incompatible Materials Strong acids. Strong oxidizing agents. Aluminum surfaces.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|-------------------------------------|---|---|
| Ethylene Glycol Monobutyl Ether 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ |
| Monoethanolamine 141-43-5 | STEL: 6 ppm TWA: 3 ppm | TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³ (vacated) Ceiling: 2 mg/m ³ | IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³ |
| Potassium hydroxide 1310-58-3 | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8 | STEL: 150 ppm TWA: 100 ppm S* | TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ (vacated) S* S* | IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³ |

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Goggles.
- Skin and Body Protection** Rubber, neoprene, or other impervious gloves are recommended to prevent skin contact. Wear appropriate chemical resistant clothing.
- Respiratory Protection** Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.
- General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-------------------------------------|-----------------------|-------------------------|----------------|
| Physical State | Liquid | Odor | Musty |
| Appearance | Brownish liquid | Odor Threshold | Not determined |
| Color | Brownish | | |
| Property | Values | Remarks • Method | |
| pH | Not determined | | |
| Melting Point/Freezing Point | Not determined | | |
| Boiling Point/Boiling Range | 95 °C / 203 °F | | |
| Flash Point | None | | |
| Evaporation Rate | Not determined | | |
| Flammability (Solid, Gas) | Liquid-Not Applicable | | |
| Upper Flammability Limits | None | | |

| | |
|-------------------------------------|--------------------|
| Lower Flammability Limit | None |
| Vapor Pressure | Not determined |
| Vapor Density | >1 |
| Specific Gravity | 1.028 |
| Water Solubility | Completely soluble |
| Solubility in other solvents | Not determined |
| Partition Coefficient | Not determined |
| Auto-ignition Temperature | Not determined |
| Decomposition Temperature | Not determined |
| Kinematic Viscosity | Not determined |
| Dynamic Viscosity | Not determined |
| Explosive Properties | Not determined |
| Oxidizing Properties | Not determined |

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Contact with incompatible materials. Keep out of reach of children. See Sec. 7 Handling & Storage.

Incompatible Materials

Strong acids. Strong oxidizing agents. Aluminum surfaces.

Hazardous Decomposition Products

When strongly heated, as in a fire, this product produces carbon dioxide, carbon monoxide and oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

| | |
|---------------------|----------------------------------|
| Eye Contact | Causes severe eye damage. |
| Skin Contact | Causes severe skin burns. |
| Inhalation | Avoid breathing vapors or mists. |
| Ingestion | May be harmful if swallowed. |

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|--|---|-----------------------|
| Ethylene Glycol Monobutyl Ether 111-76-2 | = 470 mg/kg (Rat) | = 99 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h |
| Monoethanolamine 141-43-5 | = 1720 mg/kg (Rat) | = 1 mL/kg (Rabbit) = 1000 mg/kg (Rabbit) | - |
| Potassium hydroxide 1310-58-3 | = 284 mg/kg (Rat) | - | - |
| Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8 | = 5230 mg/kg (Rat) | = 9500 mg/kg (Rabbit) | - |
| Sodium dodecyl benzene sulphonate 25155-30-0 | = 500 mg/kg (Rat) = 438 mg/kg (Rat) | - | - |

Information on physical, chemical and toxicological effects**Symptoms**

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

Not classifiable as a human carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--|-------|---------|-----|------|
| Ethylene Glycol Monobutyl Ether 111-76-2 | A3 | Group 3 | | |

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

| Chemical Name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|--|---|--|----------------------------|---|
| Ethylene Glycol Monobutyl Ether 111-76-2 | | 1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50 | | 1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50 |
| Monoethanolamine 141-43-5 | 15: 72 h Desmodesmus subspicatus mg/L EC50 | 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 3684: 96 h Brachydanio rerio mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 227: 96 h Pimephales promelas mg/L LC50 flow-through | | 65: 48 h Daphnia magna mg/L EC50 |
| Potassium hydroxide 1310-58-3 | | 80: 96 h Gambusia affinis mg/L LC50 static | | |

| | | | | |
|---|--|--|--|------------------------------------|
| Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8 | | 10000: 96 h Pimephales promelas mg/L LC50 static | | 1919: 48 h Daphnia magna mg/L LC50 |
| Sodium dodecyl benzene sulphonate 25155-30-0 | | 10.8: 96 h Oncorhynchus mykiss mg/L LC50 static | | |

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

| Chemical Name | Partition Coefficient |
|---|-----------------------|
| Ethylene Glycol Monobutyl Ether 111-76-2 | 0.81 |
| Monoethanolamine 141-43-5 | -1.91 |
| Potassium hydroxide 1310-58-3 | 0.65 0.83 |
| Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8 | -0.064 |

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

| Chemical Name | California Hazardous Waste Status |
|----------------------------------|-----------------------------------|
| Potassium hydroxide 1310-58-3 | Toxic Corrosive |

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

- UN/ID No** UN1760
- Proper Shipping Name** Corrosive liquid, n.o.s. (Potassium hydroxide)
- Hazard Class** 8
- Packing Group** II

IATA

| | |
|-----------------------------|--|
| UN/ID No | UN1760 |
| Proper Shipping Name | Corrosive liquid, n.o.s. (Potassium hydroxide) |
| Hazard Class | 8 |
| Packing Group | II |

IMDG

| | |
|-----------------------------|--|
| UN/ID No | UN1760 |
| Proper Shipping Name | Corrosive liquid, n.o.s. (Potassium hydroxide) |
| Hazard Class | 8 |
| Packing Group | II |

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| Chemical Name | TSCA | DSL | NDSL | EINECS | ELINCS | ENCS | IECSC | KECL | PICCS | AICS |
|---|---------|-----|------|---------|--------|---------|-------|---------|-------|------|
| Ethylene Glycol Monobutyl Ether | Present | X | | Present | | Present | X | Present | X | X |
| Monoethanolamine | Present | X | | Present | | Present | X | Present | X | X |
| Potassium hydroxide | Present | X | | Present | | Present | X | Present | X | X |
| Dipropylene Glycol Monomethyl Ether (DPM) | Present | X | | Present | | Present | X | Present | X | X |
| Sodium dodecyl benzene sulphonate | Present | X | | Present | | Present | X | Present | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--|--------------------------|----------------|---|
| Potassium hydroxide 1310-58-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| Sodium dodecyl benzene sulphonate 25155-30-0 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|--|------------|----------|-------------------------------|
| Ethylene Glycol Monobutyl Ether - 111-76-2 | 111-76-2 | <5 | 1.0 |
| Dipropylene Glycol Monomethyl Ether (DPM) - 34590-94-8 | 34590-94-8 | <5 | 1.0 |

CWA (Clean Water Act)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|-----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Potassium hydroxide | 1000 lb | | | X |
| Sodium dodecyl benzene sulphonate | 1000 lb | | | X |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| Ethylene Glycol Monobutyl Ether 111-76-2 | X | X | X |
| Monoethanolamine 141-43-5 | X | X | X |
| Potassium hydroxide 1310-58-3 | X | X | X |
| Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8 | X | X | X |
| Sodium dodecyl benzene sulphonate 25155-30-0 | X | X | X |

16. OTHER INFORMATION

NFPA

Health Hazards
Not determined

Flammability
Not determined

Instability
Not determined

Special Hazards
Not determined

HMIS

Health Hazards
3

Flammability
0

Physical Hazards
0

Personal Protection
Not determined

Issue Date: 01-Jun-1990
Revision Date: 16-Mar-2015
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet