

SILVER SOAK

PRE-SOAK FOR FLATWARE



CAUTION:

THIS PRODUCT CONTAINS
LESS THAN 3.5%
PHOSPHOROUS.

GOOD DTERGENCY, LOW
SUDSING, EFFECTIVE
EMULSIFIER. SAFE TO USE.

DO NOT TAKE INTERNALLY.

MAY CAUSE REDNESS AND
BURNING TO SKIN AND
EYES.

IN CASE OF CONTACT,
FLUSH THOROUGHLY WITH
RUNNING WATER FOR 15
MINUTES.

IF SWALLOWED, DO NOT
INDUCE VOMITING.

DRINK TWO LARGE
GLASSES
OF WATER OR MILK TO
DILUTE.

GET MEDICAL ATTENTION

CLEANING COMPOUND NOT
REGULATED

NET WEIGHT:

(4/9 #) 36 LBS
(4/5 #) 20 LBS

PRE-SOAK FOR SILVER AND STAINLESS STEEL FLATWARE

SILVER SOAK

FOR INDUSTRIAL USE ONLY

Chemtron

7361-H Lockport Place
Lorton, VA 22079
(703) 550-7772

KEEP OUT OF REACH OF
CHILDREN

DIRECTIONS FOR USE:

DETARNISHING SILVER:

LINE A PLASTIC DISH PAN WITH
ALUMINUM FOIL. FILL THE
DISH PAN WITH WARM WATER.

PLACE THE END OF THE
DETERGENT FEED TUBE INTO
THE DISH PAN, THEN ALLOW
THE DETERGENT TO FEED FOR
THE PREDETERMINED TIME
PERIOD. PLACE SILVERWARE
INTO DISH PAN AND ALLOW TO
SOAK FOR 10-15 MINUTES.
REMOVE AND FOLLW REGULAR
WASHING PROCEDURES.

SOAKING STAINLESS FLATWARE:

TO LOOSEN HARDENED SOILS
FROM STAINLESS FLATWARE,
FOLLOW THE SAME
PROCEDURES AS ABOVE. IT IS
NOT NECESSARY, HOWEVER,
TO LINE THE DISH PAN WITH
ALUMINUM.
ALWAYS ADD THE DETERGENT
TO THE SOAK PAN BEFORE
PLACING FLATWARE INTO IT

Chemistry And Technology For A Cleaner World